



# RIPTECH CANVAS RANGE

<b>DESCRIPTION</b>	An Acrylic-Treated Polyester Ripstop Fabric
<b>BENEFITS</b>	<ul style="list-style-type: none"> <li>✓ Waterproof</li> <li>✓ UV Resistant</li> <li>✓ Fungal Resistant</li> </ul>
<b>INTENDED USE</b>	Product is designed to be used outdoors for tenting, awnings and outdoor structures.

PROPERTY		UNITS	METHOD	300	400	500
Composition			Visual	Polyester/Acrylic	Polyester/Acrylic	Polyester/Acrylic
Construction			Visual	Woven Ripstop	Woven Ripstop	Woven Ripstop
Weight		gsm	Finlam	310 ±5%	425 ±5%	530 ±5%
Width		mm	Finlam	1 800	1 800	1 800
Water Penetration		mm/H2O	ISO 811	> 800	> 1,000	> 1,000
Tensile Strength	Warp	Newtons	BS 13934-1: 1999	> 1600	> 1800	> 1800
	Weft			> 1400	> 1500	> 1800
ColourFastness to Light*		Blue Wool	ISO 105- BO4	7	7	7
ColourFastness to Rubbing		Grey Scale	ISO 105- X12	4	4	4
Fungal Resistance			Acti-Chem M/L 13	Pass	Pass	Pass

- \* Based on olive colour  
 - Multiple colours available  
 - Fire resistant treatment available  
 - Water repellent finish available

## 2 YEAR WARRANTY

This applies to the entire range of RIPTECH™ fabrics.

The fabric is guaranteed for a period of two years, during which it covers any abnormal deterioration of the waterproofing properties and general structural integrity of the fabric, given a normal exposure to weather and in the case that care and cleaning advices summarised in this document have been properly followed. The warranty includes the replacement of the fabric required to replace the product in question, excluding other expenses such as postage, sewing, labour and / or assembly.

This warranty does not cover damages caused by accidents, mechanical action, rubbing, chemical aggressive agents, abuse and / or negligence. This warranty is applied from the date of the assembly of the product and any claim must be accompanied with the installers receipt and relevant roll number stating that the fabric used was RIPTECH™.

## CANVAS CARE INSTRUCTIONS

- Keep clean by brushing regularly with a soft bristle brush.
- Clean with clear, cold water. For localised stains, clean with a neutral detergent mixed in lukewarm water (max. 40deg) and rinse.
- Keep solvents, insecticides, petrol and other similar fluids away from canvas. Ensure canvas is thoroughly dry before packing away.

Please note that the information shared in this document is for general information only, and it is the responsibility of the customer to ensure that this product meets their specific requirements. The data in this document is for indication only and the product performance properties may vary. This document is not to be treated as a Certificate of Conformance. Hayford Traders will not entertain any damages claimed against them as a result of data expressed in this document.



	Tel: 011 314 9727 Fax: 011 314 1134 Mobile: 083 292 0710 wayne@hayfordtraders.co.za www.hayfordtraders.co.za	Unit 9 Stanford Business Park 16th Road Midrand 1685