



Unit 9, Stanford Business Park
 16th Road Midrand
www.hayfordtraders.co.za

TENCATE ROOFING

Properties:	Specification:	Test Method:
Composition	65% Polyester 35% PVA	
Coating	Acrylic	
Width (cm)	240	ISO 22198
Weight (gsm)	270	ISO 3801
Tensile Strength (daN)		
Warp (5cm)	160	ISO 13934-1
Weft (5cm)	100	
Tearing Strength (daN)		
Warp (4.3cm)	2.5	ISO 13937-1
Weft (4.3cm)	2	
Water collumn (mm)	1000	ISO 811
Colour-Weather Fastness	6 Coated side	ISO 105 B04

CANVAS CARE INSTRUCTIONS

- Keep clean by brushing regularly with a soft bristle brush.
- Clean with clear, cold water. For localised stains, clean with a neutral detergent mixed in lukewarm water (max. 40deg) and rinse.
- Keep solvents, insecticides, petrol and other similar fluids away from canvas. Ensure canvas is thoroughly dry before packing away.

Please note that the information shared in this document is for general information only and it is the responsibility of the customer to ensure that this product meets their specific requirements. The data in this document is for indication only and the product performance properties may vary. This document is not to be treated as a Certificate of Conformance. Hayford Traders will not entertain any damages claimed against them as a result of data expressed in this document.